



# Stainless Steel Tapping Sleeve

Product Release


03/2006

## Ford FTSAS All Stainless Steel Tapping Sleeve

### FEATURES

- Body, Straps and UNC threaded bolts are made of 18-8 type 304 stainless steel. Flange can be either 18-8 type 304 stainless steel or ASTM A36 carbon steel.
- All welds are fully passivated for corrosion resistance.
- Outlet style gasket is Buna-N (Nitrile) ASTM D2000.
- Removable bolts provide better accessibility.
- Other sizes and ranges available. Contact your Ford Meter Box representative for details.

All Stainless Steel Superior Design



NOM. PIPE SIZE	SLEEVE O.D. RANGE	CATALOG NUMBER		STAINLESS STEEL FLANGE SIZE CODE	OPTIONAL CARBON STEEL FLANGE SIZE CODE	No. OF BOLTS
14"	15.23-15.72	FTSAS-1572	X	14	14A	14
	15.73-16.22	FTSAS-1622				
	16.30-16.73	FTSAS-1673				
	16.74-17.26	FTSAS-1726				
16"	17.33-17.87	FTSAS-1787	X	14	14A	14
	17.88-18.43	FTSAS-1843		16	16A	20
	18.46-19.03	FTSAS-1903				
	18.87-19.45	FTSAS-1945				
18"	19.41-20.01	FTSAS-2001	X	14	14A	14
	19.88-20.48	FTSAS-2048		16	16A	20
	20.29-20.92	FTSAS-2092				
	20.93-21.57	FTSAS-2157				
20"	21.51-22.15	FTSAS-2215	X	14	14A	14
	22.16-22.81	FTSAS-2281		16	16A	20
	23.46-24.16	FTSAS-2416				
	24.82-25.52	FTSAS-2552				
24"	25.71-26.41	FTSAS-2641	X	14	14A	14
	26.55-27.25	FTSAS-2725		16	16A	20
	27.26-27.96	FTSAS-2796				
	28.14-28.84	FTSAS-2884				
30"	29.78-30.48	FTSAS-3048	X	4	4A	10
		6		6A		
	30.48-31.18	FTSAS-3118		8	8A	12
		10		10A		
	31.52-32.22	FTSAS-3222		12	12A	14
		14		14A		
	32.30-33.00	FTSAS-3300		16	16A	20
				18	18A	24
				20	20A	24
				24	24A	32
36"	35.40-36.20	FTSAS-3620	X	4	4A	10
		6		6A		
	36.20-37.00	FTSAS-3700		8	8A	12
		10		10A		
	37.00-37.80	FTSAS-3780		12	12A	14
		14		14A		
	37.60-38.30	FTSAS-3830		16	16A	20
		18		18A	24	
	38.00-38.70	FTSAS-3870		20	20A	24
		24		24A	32	
38.70-39.40	FTSAS-3940	4	4A	10		
		6	6A	12		

**To Order:** Add flange size to the appropriate sleeve number.

**Example:** A 16" Flange on 24" cast iron pipe would be FTSAS-2641-16.

**Note:** Use 1" undersize cutter for flanges 14" and larger.