



SUBMITTAL INFORMATION

Service Saddle - Single Band - (FS303W-xxx-Tap style)



TAPPED STAINLESS STEEL SADDLE WITH 7.5" WIDE BAND

Lifter Bars - ASTM A240
Type 304 stainless steel



Stainless Steel Nuts and Studs - ASTM A240 Type 304 stainless steel studs. Heavy Hex Nuts are coated to prevent galling.

Washers - Special Nylatron GS* washers are also provided for added lubrication.

*Nylatron GS is a registered trademark of the Polymer Corporation.

Stainless Taps - ASTM A240 Type 304 Stainless Steel TIG welded to shell. Available with AWWA, FIP or BSP threads 3/4" thru 2".

Pad Gasket - Buna-N D2000 Rubber.

Stainless Band - Heavy gauge ASTM A240 Type 304 Stainless Steel. 7.5" wide on 4" thru 12" sizes. All welds are fully passivated to restore stainless steel characteristics.

NOM. PIPE SIZE	SADDLE O.D. RANGE	BAND WIDTH	TAP SIZE 3/4" & 1"			TAP SIZE 1-1/4", 1-1/2" & 2"			CATALOG NUMBER	✓ SUBMITTED ITEM(S)
			No. OF BOLTS	BOLT SIZE	APPROX. WT. LBS.	No. OF BOLTS	BOLT SIZE	APPROX. WT. LBS.		
4"	4.50-4.80	7.5"	2	1/2"	2.4	2	1/2"	4.2	FS303W-480-TAP	
5"	5.56	7.5"	2	5/8"	2.7	2	5/8"	4.8	FS303W-556-TAP	
6"	6.63-6.90	7.5"	2	5/8"	2.9	2	5/8"	5.1	FS303W-690-TAP	
8"	8.63-9.05	7.5"	2	5/8"	3.3	2	5/8"	5.6	FS303W-905-TAP	
10"	10.75-11.10	7.5"	2	5/8"	6.2	2	5/8"	6.6	FS303W-1110-TAP	
12"	12.75-13.20	7.5"	2	5/8"	6.8	2	5/8"	7.1	FS303W-1320-TAP	

OUTLET TAP CODE

CC (AWWA) THREAD		
THREAD	CODE No.	✓ SUBMITTED ITEM(S)
3/4" CC	CC3	
1" CC	CC4	
1-1/4" CC	CC5	
1-1/2" CC	CC6	
2" CC	CC7	

IP THREAD		
THREAD	CODE No.	✓ SUBMITTED ITEM(S)
3/4" IP	IP3	
1" IP	IP4	
1-1/4" IP	IP5	
1-1/2" IP	IP6	
2" IP	IP7	

BSP THREAD		
THREAD	CODE No.	✓ SUBMITTED ITEM(S)
3/4" BSP	BSP3	
1" BSP	BSP4	
1-1/4" BSP	BSP5	
1-1/2" BSP	BSP6	
2" BSP	BSP7	

To Order: Select the catalog number for the desired pipe range and complete the catalog number by adding the outlet thread tap code. Example: A single band repair saddle for 9.05 O.D. pipe with a 3/4" CC thread would be FS303W-905-CC3.

FEATURES

- Body, Bands and threaded studs are made of ASTM A240 Type 304 stainless steel.
- All welds are fully passivated for corrosion resistance.
- Gasket is tapered Buna-N rubber (ASTM D2000) with circular grid.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

http://www.fordmeterbox.com

11/17/09

Submitted By: