



SUBMITTAL INFORMATION

Ball Valve Curb Stop - (B62-xxx style)



PACK JOINT FOR POLYETHYLENE PIPE (PEP) INLET BY FLARE COPPER OUTLET



Optional Padlock Wing for locking valve in closed position

Integral clamp contains machined grooves for axial restraint

Pack Joint Nut

Solid one piece tee-head and stem

Sturdy stops allow 90° motion and are enclosed and protected

EPDM O-rings in the stem

Beveled EPDM rubber gasket provides hydraulic seal

Stainless steel screw activates clamp

Anti-friction washer

Inlet

Length

A restraining ring locks the stem into the body of the valve.

Molded EPDM rubber seats support the ball.

Flare Copper Nut

Outlet

Fluorocarbon-coated brass ball

VALVE SIZE	INLET SIZE	OUTLET SIZE	LENGTH	APPROX. WT. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
3/4"	3/4"	3/4"	4-3/8"	2.6	▼ B62-333	
1"	1"	1"	5-7/16"	4.0	▼ B62-444	
1-1/2"	1-1/2"	1-1/2"	7-3/4"	12.6	▼▼ B62-666 -IDR7	
2"	2"	2"	8-9/16"	16.0	▼▼ B62-777 -IDR7	

▼ UL Classified to ANSI/NSF Standard 61.

▼▼ Add "-K" to end of catalog number for item to be UL classified to ANSI/NSF Standard 61.

Note: Ford recommends using insert stiffeners with plastic pipe or tubing.



FEATURES

- All brass conforms to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- Valve is non-directional and is watertight with flow in either direction.
- Ends are integral or secured with adhesive to prevent unintentional disassembly.
- Hole for attaching curb box rod or handle is provided in tee-head.
- 300 PSI working pressure.

Optional Padlock Wing for locking valve in closed position. Insert "W" into part number.

Optional full 360° tee-head rotation. Insert "R" into of part number.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

<http://www.fordmeterbox.com>

10/23/07

Submitted By: