



# SUBMITTAL INFORMATION

## "U" Branch Piece - (U48-xx-xx style)



PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS) INLET BY TWO MALE IRON PIPE THREAD OUTLETS



DESCRIPTION		LENGTH	SPACING	APPROX. WT. LBS	PART NUMBER	✓ SUBMITTED ITEM(S)
PACK JOINT INLET	MIP OUTLET					
3/4"	Two - 3/4"	3-1/16"	6-1/2"	1.8	▼ U48-33-65	
3/4"	Two - 3/4"	3-1/16"	7-1/2"	2.1	*▼ U48-33	
1"	Two - 3/4"	3-3/16"	6-1/2"	1.8	▼ U48-43-65	
1"	Two - 3/4"	3-3/16"	7-1/2"	2.7	*▼ U48-43	
1"	Two - 3/4"	3-3/16"	12-1/2"	3.0	▼ U48-43-125	
1"	Two - 3/4"	3-3/16"	14"	3.1	▼ U48-43-14	
1-1/2"	Two - 3/4"	3-3/8"	7-1/2"	3.2	*▼▼ U48-63	

\* 7-1/2" spacing is standard and will be provided unless otherwise specified.

▼ UL Classified to ANSI/NSF Standard 61.

▼▼ Add "-K" to end of catalog number for item to be UL classified to ANSI/NSF Standard 61.

**Note:** Ford recommends using insert stiffeners with plastic pipe or tubing.



### FEATURES

- All brass conforms to AWWA Standard C800 (ASTM B-62 and ASTM B-584, UNS NO C83600 - 85-5-5-5)
- 7-1/2" spacing will be provided unless otherwise specified.

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



**The Ford Meter Box Company, Inc.**

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

<http://www.fordmeterbox.com>

07/19/04

Submitted By: