

## INSTALLATION INSTRUCTIONS FOR THE STANDARD FORD PIT SETTER

1. Dig trench to proper depth for Pit Setter and lid, also allow for bottom support and drainage.
2. Place crushed gravel or an even layer of concrete blocks in the bottom of hole; if using a bottom plate, place in hole before installing the Pit Setter.
3. Lower the pit setter in the hole so the top of the chosen cover will be flush with the final grade level.
4. Connect the inlet and outlet service lines to the Pit Setter placing an additional wrench on the wrench flats to avoid unintentionally twisting the tubing.
5. Pressure test the Pit Setter prior to backfilling to ensure all valves and joints are secured tightly and no leaks are detected.
6. **IMPORTANT:** Carefully backfill around the tile up to 12" at a time, tamping each layer. Improper backfill may distort tile.
7. Evenly center the cover on the tile and complete backfilling to the final top lid grade level.

### WARRANTY – READ BEFORE INSTALLING

All merchandise is warranted to be free from defects in materials and factory workmanship. We will provide, free of charge, new products in equal quantities for any that prove defective within one year from date of shipment from our factory. Manufacturer shall not be liable for any loss, damage, or injury, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use and user assumes all risk and liability whatever in connection therewith. No claims for labor or consequential damage will be allowed. The foregoing may not be changed except by agreement signed by an officer of the manufacturer.

No other warranties are applicable or may be implied, including the implied warranty of merchantability and the implied warranty of fitness for particular purpose and any warranty relating to infringement or the like, all of which are disclaimed.

**DAMAGE CAUSED BY IMPROPER TOOLS OR HANDLING  
WILL VOID OUR WARRANTY**

### THE FORD METER BOX COMPANY, INC.

P.O. Box, Wabash, Indiana, USA 46992-0443

Phone:260-563-3171 - Domestic FAX:800-826-3487

Overseas FAX:260-563-0167 - Internet: [www.fordmeterbox.com](http://www.fordmeterbox.com)

