

Style A and B Wall Setters

Tandem Inside Settings for special metering applications

Ford Wall Setters are designed to allow a utility to install a meter and a pressure regulator in a single setting. Please specify the length of the regulators when ordering.

Style "A" Description: Setter including integral check valve, meter nuts and adapters for pressure regulator.

Style "B" Description: Setter including meter nuts and adapters for pressure regulator.

Each end of the Wall Setter body has 3/4" male iron pipe threads for a variety of couplings, valves and check valves.



Style A Wall Setter with
Optional Valves

Style "A" Integral Check Wall Setter for 5/8" and 5/8"x3/4" Meters

CATALOG NUMBER	DESCRIPTION	METER NUT SPACING	COUPLINGS AND ADAPTERS INCLUDED
WSB	Bracket for wall mounting	-	-
Clamp-32	Stainless Steel Clamp for above	-	-
WS88-133A	Setter for 5/8" meter including meter nuts, adapter, etc.	15-5/8"	One RA-1, one C38-13-2.188
WS88-233A	Setter for 5/8"x3/4" meter including meter nuts, adapter, etc.	15-1/4"	One RA-2, one C38-23-1.625

NOTE: Couplings, adapters and optional items will be packaged separately from Wallsetters.



Style B Wall Setter with
Optional Valves

Style "B" Wall Setter for 5/8", 5/8"x3/4" and 3/4" Meters

CATALOG NUMBER	DESCRIPTION	METER NUT SPACING	COUPLINGS AND ADAPTERS INCLUDED
WSB	Bracket for wall mounting	-	-
Clamp-32	Stainless Steel Clamp for above	-	-
WS88-133B	Setter for 5/8" meter including meter nuts, adapter, etc.	15-5/8"	One RA-1, one C38-13-2.188
WS88-233B	Setter for 5/8"x3/4" meter including meter nuts, adapter, etc.	15-1/4"	One RA-2, one C38-23-1.625
WS88-333B	Setter for 3/4" meter including meter nuts, adapter, etc.	16-3/4"	One RA-2, one C38-23-1.625

NOTE: Couplings, adapters and optional items will be packaged separately from Wallsetters.

All Wallsetters have a spacing to include a 4-1/2" long PRV with 3/4" FIP thread connections.