

Ford Tandem Coppersetters

Designed to solve problems resulting from excessive water pressure, the Tandem Coppersetter holds a pressure regulator just ahead of the water meter – all in one compact, quickly-installed Ford Coppersetter device. Pressure of the water flow through the meter and customer service lines is thereby easily reduced.

This space-saving unit is designed for installation in a single meter pit, frequently as small as 20" in diameter.

Ford recommends service lines and valves be set a minimum of 2" from the pit wall to help prevent freezing.



TV72-15W-44-33

HOW TO ORDER

Select Coppersetter Series desired. Add the letter "T" before Catalog Number selected. EXAMPLE: TV72-18W-21-33 = Valve type Tandem Coppersetter for 5/8" x 3/4" meter, 18" high with 3/4" flared copper inlet and with double purpose union swivel outlet. Tandem Coppersetters include an "S" tube and male iron pipe adapters for holding a pressure regulator. When ordering a 5/8", 5/8" x 3/4" or 3/4" Coppersetter, adapters and "S" tube will be sized to hold a 3/4" regulator with an overall length between 4" and 5". When ordering a 1" Coppersetter, adapters and "S" tube will be sized to hold a 1" regulator with an overall length between 5" and 6". Unless specified otherwise, Tandem Coppersetters are designed to hold a water meter in series with a pressure regulator. **An "S" tube and male iron pipe adapters for the regulator are included.**

Adapters for Regulator



CATALOG NUMBER	METER SIZE	ADAPTER LENGTH	APPROX. WT. LBS.
RA-1	5/8"	1-7/8"	.6
RA-2	5/8"x3/4"	2-1/16"	.8
RA-4	1"	2-1/4"	1.3