

Ford Angle Ball Flanged Meter Valves

For 1-1/2" and 2" Meters



LXI Products meet
ANSI/NSF Standard 61
see page 2

BFA13-777W



Female Iron Pipe Thread by Meter Flange

| CATALOG NUMBER | DESCRIPTION | | | APPROX. WT. LBS. |
|----------------|-------------|------------|-------------------|------------------|
| | VALVE SIZE | INLET SIZE | METER SIZE OUTLET | |
| BFA13-666W | 1-1/2" | 1-1/2" | 1-1/2" | 8.3 |
| BFA13-777W | 2" | 2" | 1-1/2" and 2" | 11.2 |

Flare Copper by Meter Flange

| CATALOG NUMBER | DESCRIPTION | | | APPROX. WT. LBS. |
|----------------|-------------|------------|-------------------|------------------|
| | VALVE SIZE | INLET SIZE | METER SIZE OUTLET | |
| BFA23-666W | 1-1/2" | 1-1/2" | 1-1/2" | 9.5 |
| BFA23-777W | 2" | 2" | 1-1/2" and 2" | 14.6 |

Pack Joint for Copper or Plastic Tube by Meter Flange

| CATALOG NUMBER | DESCRIPTION | | | APPROX. WT. LBS. |
|----------------|-------------|------------|-------------------|------------------|
| | VALVE SIZE | INLET SIZE | METER SIZE OUTLET | |
| *♦ BFA43-666W | 1-1/2" | 1-1/2" | 1-1/2" | 9.0 |
| *♦ BFA43-777W | 2" | 2" | 1-1/2" and 2" | 14.9 |

NOTE: "W" indicates valve is standard with Padlock Wings only.

1-1/2" and 2" Angle Ball Meter Valves are suitable for a customer side shut off (outlet side of meter) up to 150 PSI.

Standard features include: Flat drop-in gaskets for 1-1/2" and 2" flanged valves. Slotted holes are standard on 2" Flanged Angle Valves, adapting them for connection to either 1-1/2" or 2" flanged meters.

Options Available

* **Grip Joint** for CTS is available. Add "-G" to end of catalog number.

♦ **Quick Joint** is available by adding a "-Q" to the end of the catalog number.

Handles are available for Ball Valves; see page 37.

For Reclaimed Water Tee-head for Ball Valves, insert "RW" into the catalog number. Example: BFARW43-666W. Tee-head sold only with padlock wing.

Meter Support Brackets to support the meter during installation are available on flanged valves at additional cost.

Add "MSB" to the catalog number. Example: BFA43-777W-MSB.

Standard tee-head stops on the body to permit 90° turn *only*. **Full 360° tee-head rotation** is available. Add "R" to catalog number.

Example: BFA13-777WR.

Steel Bolts and Nuts (5/8"x2-1/2", zinc plated) for attaching 1-1/2" and 2" valves to meters are available, but must be ordered separately. Steel bolt catalog number: PSB

2" Gate Valve Operating Nut is available for 1-1/4" through 2" Ball Valves and can be ordered from page 38.

See page 5 for specific details on above options.