



LXI Products meet  
ANSI/NSF Standard 61  
see page 2

# Ford Ball Service Valves - Continued

5/8" Ball Valves with Drain/Test Valve  
on Outlet Side of Valves

B11-233D



## Female Iron Pipe Thread Both Ends

CATALOG NUMBER	DESCRIPTION			APPROX. LENGTH	APPROX. WT. LBS.
	VALVE SIZE	INLET SIZE	OUTLET SIZE		
B11-211D	5/8"	1/2"	1/2"	2-15/16"	1.2
B11-231D	5/8"	3/4"	1/2"	2-15/16"	1.3
B11-233D	5/8"	3/4"	3/4"	2-15/16"	1.2

B21-233D



## Flare Copper Inlet by Female Iron Pipe Outlet

CATALOG NUMBER	DESCRIPTION			APPROX. LENGTH	APPROX. WT. LBS.
	VALVE SIZE	FLARE SIZE	FIP SIZE		
B21-231D	5/8"	3/4"	1/2"	3-9/16"	1.8
B21-233D	5/8"	3/4"	3/4"	3-9/16"	1.8

**Note:** Length of valve for flare copper is measured less the copper tube nut.

B41-233D



## Pack Joint for Copper or Plastic Tubing (CTS) Inlet by Female Iron Pipe Thread Outlet

CATALOG NUMBER	DESCRIPTION			APPROX. LENGTH	APPROX. WT. LBS.
	VALVE SIZE	CTS SIZE	FIP SIZE		
* B41-233D	5/8"	3/4"	3/4"	3-15/16"	1.6

**Note:** Length of valve for Pack Joints is measured less the Pack Joint nut.

## Options Available

\* **Grip Joint for CTS** is available. Add "-G" to the end of the catalog number. Example: B41-233D-G.

**Padlock Wings** - All valves are available with padlock wings. Add "W" to catalog number.

Standard tee-head stops within the body to permit 90° turn *only*. **Full 360° tee-head rotation** is available. Add "R" to catalog number. Example: B41-233D-R.

**Lock Caps** are available for 5/8" through 2" Ball Valves and can be ordered from page 38.

**Handles** are available for Ball Valves; see page 37.

See page 5 for specific details on above options.