



LXI Products meet
ANSI/NSF Standard 61
see page 3



Meter Coupling Nuts Only

CATALOG NUMBER	DESCRIPTION	APPROX. WT. LBS.	STD. PKG. QTY.
MN-1	5/8" Meter coupling Nut Only for "A" and "C" Body Style Straight Meter Couplings	.14	-
CMC	5/8" to 3/4" Changeover Meter Coupling Nut for Changing 5/8" "A" Body Style Coupling from 5/8" meter to 5/8"x3/4" Meter	.23	50
MN-2	3/4" Meter coupling Nut Only for "A" and "C" Body Style Straight Meter Couplings	.24	-
MN-4	1" Meter coupling Nut Only for "A" and "C" Body Style Straight Meter Couplings	.31	-
MN-7	2" Meter coupling Nut Only for "A" and "C" Body Style Straight Meter Couplings	-	-

Straight Meter Couplings

Straight Meter Couplings by Male Iron Pipe Thread



Body Style A
(hex on barrel)



Body Style B
(heavy hex on barrel)



Body Style C
(short with inside wrench hex)

CATALOG NUMBER	DESCRIPTION OF COUPLING			APPROX. WEIGHT LBS.	STANDARD PACKAGE QUANTITY
	BODY STYLE	MALE IRON PIPE THREAD SIZE	COUPLING LENGTH		
FOR 5/8" METERS					
C38-11-2	A	1/2"	2"	.3	50
C38-11-2.188	A	1/2"	2-3/16"	.4	50
** C38-11-2.375	A	1/2"	2-3/8"	.4	40
C38-13-2.188	B	3/4"	2-3/16"	.4	40
FOR 5/8" x 3/4" AND 3/4" METERS					
C38-21-1.625	B	1/2"	1-5/8"	.5	-
C38-21-2.375	A	1/2"	2-3/8"	.6	25
C38-23-1.437	C	3/4"	1-7/16"	.4	35
C38-23-1.5	C	3/4"	1-1/2"	.4	35
C38-23-1.625	C	3/4"	1-5/8"	.4	35
C38-23-2	A	3/4"	2"	.5	30
C38-23-2.25	A	3/4"	2-1/4"	.5	25
** C38-23-2.5	A	3/4"	2-1/2"	.5	25
C38-23-2.75	A	3/4"	2-3/4"	.5	25
C38-23-3	A	3/4"	3"	.5	25
C38-23-8.5	A	3/4"	8-1/2"	1.6	35
C38-23-12	B	3/4"	12"	2.3	25
C38-24-2.5	B	1"	2-1/2"	.6	24
FOR 1" METERS					
C38-44-1.5	C	1"	1-1/2"	.6	20
C38-44-2	C	1"	2"	.6	18
C38-44-2.25	B	1"	2-1/4"	.8	18
** C38-44-2.625	A	1"	2-5/8"	.7	15
C38-44-3.5	A	1"	3-1/2"	.7	15
C38-44-8.5	A	1"	8-1/2"	1.6	5
FOR 1-1/4" METERS					
C38-54-2.75	A	1"	2-3/4"	1.2	12
FOR 1-1/2" METERS					
C38-66-2.875	A	1-1/2"	2-7/8"	1.8	8
FOR 2" METERS					
C38-77-3.0625	A	2"	3-1/16"	3.0	4

** Standard Coupling Length

Straight Meter Couplings by Female Iron Pipe Thread and Flare Copper



CATALOG NUMBER	DESCRIPTION	COUPLING LENGTH	APPROX. WT. LBS.	STD. PKG. QTY.
METER SWIVEL NUT BY FEMALE IRON PIPE THREAD				
C31-13	5/8" Meter x 3/4" Female Iron Pipe	1-7/8"	0.5	30
C31-23	5/8"x3/4" & 3/4" Meter x 3/4" Female Iron Pipe	1-3/4"	0.6	30
C31-24	5/8"x3/4" & 3/4" Meter x 1" Female Iron Pipe	2"	0.7	25
C31-44	1" Meter x 1" Female Iron Pipe	2-3/8"	0.9	15
C31-45	1" Meter x 1-1/4" Female Iron Pipe	2-3/8"	1.1	12
METER SWIVEL NUT BY FLARE COPPER				
C32-13	5/8" Meter x 3/4" Flare Copper	2-3/16"	0.8	20
C32-23	5/8"x3/4" & 3/4" Meter x 3/4" Flare Copper	2-3/16"	0.9	20
C32-44	1" Meter x 1" Flare Copper	2-1/2"	1.4	12

Note: Length of couplings for Flare Copper is measured less the Copper tube nut.

Options Available

No-Lead alloy is available, add "-NL" to the end of the catalog number. With the No-Lead option, brass components in contact with potable water shall be of No-Lead Alloy, UNS/CDA No. C89833. Brass components that do not come in contact with potable water shall be UNS/CDA No. C83600.

Straight Meter Couplings With Pack Joints



LXI Products meet
ANSI/NSF Standard 61
see page 3



CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.	STD. PKG. QTY.
METER SWIVEL NUT BY PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS)					
C34-11	5/8" Meter	x	1/2" CTS P.J.	.7	25
◆ C34-13	5/8" Meter	x	3/4" CTS P.J.	.7	20
C34-21	5/8"x3/4" & 3/4" Meter	x	1/2" CTS P.J.	.9	20
C34-22	5/8"x3/4" & 3/4" Meter	x	5/8" CTS P.J.	.8	-
◆ C34-23	5/8"x3/4" & 3/4" Meter	x	3/4" CTS P.J.	.8	18
◆ C34-24	5/8"x3/4" & 3/4" Meter	x	1" CTS P.J.	.9	15
◆ C34-44	1" Meter	x	1" CTS P.J.	1.2	12
C34-45	1" Meter	x	1-1/4" CTS P.J.	1.7	8
METER SWIVEL NUT BY PACK JOINT FOR IRON PIPE					
C35-11	5/8" Meter	x	1/2" Iron Pipe P.J.	.6	24
C35-13	5/8" Meter	x	3/4" Iron Pipe P.J.	.6	20
C35-21	5/8"x3/4" & 3/4" Meter	x	1/2" Iron Pipe P.J.	.7	20
C35-23	5/8"x3/4" & 3/4" Meter	x	3/4" Iron Pipe P.J.	.8	18
C35-23-4.875	5/8"x3/4" & 3/4" Meter	x	3/4" Iron Pipe P.J.	1.2	10
C35-44	1" Meter	x	1" Iron Pipe P.J.	1.5	10
METER SWIVEL NUT BY PACK JOINT FOR PE PIPE					
C36-13	5/8" Meter	x	3/4" PE Pipe P.J.	.9	20
C36-23	5/8"x3/4" & 3/4" Meter	x	3/4" PE Pipe P.J.	.9	15
C36-44	1" Meter	x	1" PE Pipe P.J.	1.8	8
METER SWIVEL NUT BY PACK JOINT FOR PVC PIPE					
C37-13	5/8" Meter	x	3/4" PVC Pipe P.J.	.8	20
C37-21	5/8"x3/4" & 3/4" Meter	x	1/2" PVC Pipe P.J.	.7	-
C37-23	5/8"x3/4" & 3/4" Meter	x	3/4" PVC Pipe P.J.	.9	15
C37-44	1" Meter	x	1" PVC Pipe P.J.	1.7	8

Grip Joint for CTS and PEP is available. Add "-G" to the catalog number.

◆ **Quick Joint** can be ordered by adding "-Q" to the catalog number.

Note: Insert Stiffeners are listed on page 7 of this section.

Angle Meter Couplings



CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.	STD. PKG. QTY.
METER SWIVEL NUT BY FEMALE IRON PIPE THREAD					
L31-13	5/8" Meter	x	3/4" Female Iron Pipe	.6	20
L31-23	5/8"x3/4" & 3/4" Meter	x	3/4" Female Iron Pipe	.8	20
L31-23D (Test Valve)	5/8"x3/4" & 3/4" Meter	x	3/4" Female Iron Pipe	.9	15
L31-24	5/8"x3/4" & 3/4" Meter	x	1" Female Iron Pipe	.9	15
L31-44	1" Meter	x	1" Female Iron Pipe	1.2	12
METER SWIVEL NUT BY FLARE COPPER					
L32-12	5/8" Meter	x	5/8" Flare Copper	.8	16
L32-13	5/8" Meter	x	3/4" Flare Copper	.8	16
L32-23	5/8"x3/4" & 3/4" Meter	x	3/4" Flare Copper	1.0	14
L32-44	1" Meter	x	1" Flare Copper	1.6	8
METER SWIVEL NUT BY MALE IRON PIPE THREAD					
L38-11	5/8" Meter	x	1/2" Male Iron Pipe	.4	30
L38-23	5/8"x3/4" & 3/4" Meter	x	3/4" Male Iron Pipe	.7	16
L38-24	5/8"x3/4" & 3/4" Meter	x	1" Male Iron Pipe	.7	15
L38-44	1" Meter	x	1" Male Iron Pipe	1.1	10
L38-45-AWT	1" Meter	x	1-1/4" Male Iron Pipe	1.3	-
L38-66	1-1/2" Meter	x	1-1/2" Male Iron Pipe	3.0	6
METER SWIVEL NUT BY PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS)					
L34-13	5/8" Meter	x	3/4" CTS P.J.	.8	15
◆ L34-23	5/8"x3/4" & 3/4" Meter	x	3/4" CTS P.J.	1.0	15
L34-44	1" Meter	x	1" CTS P.J.	1.3	8
L34-45	1" Meter	x	1-1/4" CTS P.J.	.9	6
METER SWIVEL NUT BY PACK JOINT FOR PE PIPE					
L36-23	5/8"x3/4" & 3/4" Meter	x	3/4" PE Pipe P.J.	1.1	14
L36-44	1" Meter	x	1" PE Pipe P.J.	1.9	6

Grip Joint for CTS and PEP is available. Add "-G" to the catalog number.

◆ **Quick Joint** can be ordered by adding "-Q" to the catalog number.

Options Available

No-Lead alloy is available, add "-NL" to the end of the catalog number. With the No-Lead option, brass components in contact with potable water shall be of No-Lead Alloy, UNS/CDA No. C89833. Brass components that do not come in contact with potable water shall be UNS/CDA No. C83600.