



LXI Products meet
ANSI/NSF Standard 61
see page 2

Single Check Valves (continued)

Straight Check Valves (In-Line Accessible)



HS31-323

METER SWIVEL NUT INLET BY FEMALE IRON PIPE THREAD OUTLET

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	METER SIZE INLET	OUTLET SIZE	
HS31-313	3/4"	5/8"	3/4"	1.2
Δ HS31-323	3/4"	5/8"x3/4" & 3/4"	3/4"	1.4
Δ HS31-444	1"	1"	1"	1.7



HS38-323

METER SWIVEL NUT INLET BY MALE IRON PIPE THREAD OUTLET

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	METER SIZE INLET	OUTLET SIZE	
Δ HS38-323	3/4"	5/8"x3/4" & 3/4"	3/4"	1.3
HS38-444	1"	1"	1"	1.6

METER SWIVEL NUT INLET BY FLARE COPPER OUTLET

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	METER SIZE INLET	OUTLET SIZE	
HS32-323	3/4"	5/8"x3/4" & 3/4"	3/4"	1.8



HS34-323

METER SWIVEL NUT INLET BY PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS)* OUTLET

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	METER SIZE INLET	OUTLET SIZE	
HS34-323	3/4"	5/8"x3/4" & 3/4"	3/4"	1.6

*Grip Joint for CTS is available. See options for ordering information.



HS11-333

FEMALE IRON PIPE THREAD INLET BY FEMALE IRON PIPE THREAD OUTLET

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	INLET SIZE	OUTLET SIZE	
HS11-333	3/4"	3/4"	3/4"	1.2
HS11-444	1"	1"	1"	1.4
HS11-666	1-1/2"	1-1/2"	1-1/2"	5.7
HS11-777	2"	2"	2"	8.2

Options Available

Grip Joint for CTS or PEP can be ordered by adding "-G" to the end of catalog number. EXAMPLE: HA34-323-G

Δ **Indicates Drain/Test Valve available.** Add "D" to catalog number. EXAMPLE: HA31-323D

No-lead alloy is available; add "-NL" to the end of the catalog number. With the no-lead option, brass components in contact with potable water shall be of no-lead alloy, UNS/CDA No. C89833. Brass components that do not come in contact with potable water shall be UNS/CDA No. C83600.

Single Check Valves (continued)

Straight Check Valves (In-Line Accessible)



LXI Products meet
ANSI/NSF Standard 61
see page 2



HS81-333

MALE IRON PIPE THREAD INLET BY FEMALE IRON PIPE THREAD OUTLET

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	INLET SIZE	OUTLET SIZE	
Δ HS81-333	3/4"	3/4"	3/4"	1.2
Δ HS81-444	1"	1"	1"	1.4

MALE IRON PIPE THREAD BY PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS)

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	INLET SIZE	OUTLET SIZE	
HS84-333	3/4"	3/4"	3/4"	-



HS88-333

MALE IRON PIPE THREAD BOTH ENDS

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	INLET SIZE	OUTLET SIZE & TYPE	
HS88-333	3/4"	3/4"	3/4"	1.1

PACK JOINT FOR COPPER OR PLASTIC TUBING (CTS) BOTH ENDS

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	INLET SIZE	OUTLET SIZE & TYPE	
HS44-333	3/4"	3/4"	3/4"	1.8



HS91-323

METER YOKE INLET BY FEMALE IRON PIPE

CATALOG NUMBER	DESCRIPTION			APPROX. WT. LBS.
	VALVE SIZE	METER INLET SIZE	OUTLET SIZE & TYPE	
Δ HS91-313	3/4"	5/8"	3/4" FIP	1.3
Δ HS91-323	3/4"	5/8"x3/4" & 3/4"	3/4" FIP	1.3
HS91-344	3/4"	1"	1" FIP	-
HS91-444	1"	1"	1" FIP	1.7

Options Available

Grip Joint for CTS or PEP can be ordered by adding "-G" to the end of catalog number. EXAMPLE: HA34-323-G

Δ **Indicates Drain/Test Valve available.** Add "D" to catalog number. EXAMPLE: HA31-323D

No-lead alloy is available; add "-NL" to the end of the catalog number. With the no-lead option, brass components in contact with potable water shall be of no-lead alloy, UNS/CDA No. C89833. Brass components that do not come in contact with potable water shall be UNS/CDA No. C83600.