


SUBMITTAL INFORMATION

Stainless Steel Tapping Sleeve - (FAST-xxxx-xA style)



STAINLESS STEEL TAPPING SLEEVE WITH CARBON STEEL FLANGE

Flange - Carbon steel flange per AWWA C207 with recess per MSS SP-60 to accept standard tapping valves.

Outlet Pipe - 18-8 type 304 stainless steel. Schedule 10 for 3" and 4" outlets. Outlets larger than 4" are Schedule 5.

Lifter bar - Type 304 stainless steel provides a heavy bearing surface for nuts.

Studs, nuts, & washers - Type 304 stainless steel. Nuts and washers are coated to prevent galling.

3/4-14 No-Lead Brass Test Plug

Armors - Heavy gage Type 304 stainless steel are vulcanized to gasket to bridge the gap between lugs.



Outlet Gasket - Virgin NBR (Buna-N) compounded for water service, per ASTM D2000. Outlet gasket ensures complete seal of outlet area.

Body & Strap — Type 304, stainless steel all welds are fully passivated to restore stainless characteristics.

Full Gasket - Gridded Virgin SBR compounded for water service, per ASTM D2000. Full gasket gives 360° pipe coverage.

NOM. PIPE SIZE	SLEEVE O.D. RANGE	CATALOG NUMBER**	BY	OUTLET SIZE/CODE	APPROX. Wt.	NOM. DIM. - INCHES				SADDLE THICKNESS (GAGE)	STRAP THICKNESS (GAGE)	STUD SIZE	No. STUDS	✓ SUBMITTED ITEM(S)
						A	B	C	D					
16"	17.30 - 17.70	FAST-1770-xA	X	3	75	4-1/64"	3-1/4"	5-3/16"	15	.105" (12)	.063" (16)	5/8"	15	
	17.40 - 17.80	FAST-1780-xA		4	75	5-1/64"	4-1/4"	5-3/16"	16				15	
	17.75 - 18.15	FAST-1815-xA		6	79	7-1/64"	6-3/8"	5-1/2"	16				15	
	18.15 - 18.62	FAST-1862-xA		8	100	9-1/64"	8-5/16"	5-5/8"	20				18	
	18.60 - 19.00	FAST-1900-xA		10	105	11-1/64"	10-1/4"	6-1/8"	20				18	
	18.80 - 19.20	FAST-1920-xA		12	141	13-1/64"	12-1/4"	6-1/4"	24				21	
18"	19.30 - 19.70	FAST-1970-xA	X	3	75	4-1/64"	3-1/4"	5-3/16"	15	.105" (12)	.063" (16)	5/8"	15	
	19.40 - 19.80	FAST-1980-xA		4	75	5-1/64"	4-1/4"	5-3/16"	16				15	
	19.50 - 19.92	FAST-1992-xA		6	79	7-1/64"	6-3/8"	5-1/2"	16				15	
	19.80 - 20.20	FAST-2020-xA		8	100	9-1/64"	8-5/16"	5-5/8"	20				18	
				10	105	11-1/64"	10-1/4"	6-1/8"	20				18	
				12	141	13-1/64"	12-1/4"	6-1/4"	24				21	
20"	20.20 - 20.60	FAST-2060-xA	X	3	75	4-1/64"	3-1/4"	5-3/16"	15	.105" (12)	.063" (16)	5/8"	15	
	20.90 - 21.30	FAST-2130-xA		4	75	5-1/64"	4-1/4"	5-3/16"	16				15	
	21.20 - 21.60	FAST-2160-xA		6	79	7-1/64"	6-3/8"	5-1/2"	16				15	
	21.40 - 21.80	FAST-2180-xA		8	100	9-1/64"	8-5/16"	5-5/8"	20				18	
	21.86 - 22.26	FAST-2226-xA		10	105	11-1/64"	10-1/4"	6-1/8"	20				18	
	22.30 - 22.70	FAST-2270-xA		12	141	13-1/64"	12-1/4"	6-1/4"	24				21	
24"	23.80-24.20	FAST-2420-xA	X	3	75	4-1/64"	3-1/4"	5-3/16"	15	.105" (12)	.063" (16)	5/8"	15	
	24.30-24.70	FAST-2430-xA		4	75	5-1/64"	4-1/4"	5-3/16"	16				15	
	24.80-25.20	FAST-2440-xA		6	79	7-1/64"	6-3/8"	5-1/2"	16				15	
	25.30-25.70	FAST-2450-xA		8	100	9-1/64"	8-5/16"	5-5/8"	20				18	
	25.80-26.20	FAST-2460-xA		10	105	11-1/64"	10-1/4"	6-1/8"	20				18	
				12	141	13-1/64"	12-1/4"	6-1/4"	24				21	

Highlighted ranges are recommended for ductile iron pipe and C905 PVC applications.

** To order: Add flanged outlet size to catalog number. Example: The complete FAST catalog number for an 20" pipe (21.60 O.D.) with a 12" carbon steel flange is FAST-2160-12A.

FEATURES

- Body, straps and UNC threaded studs are made of type 304 stainless steel
- Flange is ASTM A36 carbon steel
- All sleeves are fully passivated for corrosion resistance
- Outlet gasket is NBR (Buna-N) rubber per ASTM D2000
- UL classified to ANSI/NSF standard 61

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

08/23/18

Submitted By: