



SUBMITTAL INFORMATION

Quick Joint Swivel Eighth Bend Coupling - (LA04-44S-AWT-Q-NL style)



SWIVEL NUT INLET BY QUICK JOINT FOR COPPER OR PLASTIC TUBING (CTS) OUTLET, ASSEMBLED WATERTIGHT



| DESCRIPTION | | LENGTH | HEIGHT | APPROX. WT. LBS | PART NUMBER | ✓ SUBMITTED ITEM(S) |
|-------------|--------------|----------|----------|-----------------|-------------------|---------------------|
| SWIVEL NUT | Q.J. FOR CTS | | | | | |
| 1" | 1" | 1-21/64" | 2-39/64" | 2.1 | LA04-44S-AWT-Q-NL | |

Note: Ford recommends insert stiffeners when using plastic tubing.

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5)
- Swivel nut inlet allows proper outlet positioning without compromising installation torque
- Copper gasket included to ensure proper inlet seal

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

04/30/18

Submitted By: